

WEIGHT ONLY OR
PRICE COMPUTING SCALES

DPOS-400 series



Dimensions

DATA IN mm

A	50
B	275
C	65
D	345
E	420
F	45




Plate dimensions: L300 x W230 mm.
Weight with packaging: 5 kg.



LCD
GRAPHIC
DISPLAY



RS-232



USB



METROLOGICAL
VERIFICATION
OPTIONAL (EU)

Models

Flat format

	Vendor display	Buyer display	Communication protocols	Power	Capacity / Accuracy	Reference
DPOS-400 F - 1 DISP.	Graphic LCD	-	Up to 100	USB	6 kg / 2 g - 15 kg / 5 g	7POSP00LNE_
DPOS-400 F - 2 DISP.	Graphic LCD	Graphic LCD	Up to 100	USB	6 kg / 2 g - 15 kg / 5 g	7POSPP0LNE_

Pole format

	Vendor display	Buyer display	Communication protocols	Power	Capacity / Accuracy	Reference
DPOS-400 P - 1 DISP.	Graphic LCD	-	Up to 100	USB	6 kg / 2 g - 15 kg / 5 g	7POST00LNE_
DPOS-400 P - 2 DISP.	Graphic LCD	Graphic LCD	Up to 100	USB	6 kg / 2 g - 15 kg / 5 g	7POSTT0LNE_
DPOS-400 P - 2 DISP. (1 in base and 1 in pole)	Graphic LCD	Graphic LCD	Up to 100	USB	6 kg / 2 g - 15 kg / 5 g	7POSPT0LNE_

M optional

Characteristics and functionality

Main characteristics

- Weight only or price computing scale for checkout applications.
- Modular and modern design.
- Easy integration into counters.
- Valid for legal metrology.

Features

- Tare, fix tare and manual zero.
- Display of price in a secondary currency.
- Energy saving via programmable on and off back lighting switching and automatic disconnection.
- Power supply and communications through one single USB cable.

Capacity / Accuracy

- Multi-range (3,000 divisions): 6 kg / 2 g - 15 kg / 5 g.
- Optional:
 - > Mono-range (3,000 divisions): 15 kg / 5 g.

Available formats

- Flat.
- Pole.

Construction

- Structure:
 - > ABS plastic casing.
- Displays:
 - > Easy to install in multiple positions (1 or 2 displays).
 - > Backlit LCD matrix graphic display.
 - > 5 digits (up to H20 mm) per display.
 - > Shows only weight or weight, price/kg and total (connected to POS and depending on the communication protocol).
- Keypad with 3-keys.
- Plate:
 - > Type: flat.
 - > Material: stainless steel.

Communication to PC / POS / ECR

- USB and RS-232 interfaces.
- Communication protocols available for the main POS and ECR in the market.
- Multi-protocol: communication protocol is selected in the scale (more than 50 protocols available).

Power supply

- Power via USB connection from a PC, POS, ECR, etc.

Energy consumption

- 1 W (approx.).

Options

Option	Characteristics	Ref.
15 kg / 5 g capacity	Mono-range (3,000 divisions).	...N_ _ (*)
Metrological verification (M)	Metrological verification (M), according to EU weighing directives. (See section on equipment metrological verification).	Consult

(*) The scale references with this capacity are obtained by replacing the last characters of the reference for the standard scale with the indicated ending.

Accessories

USB 5 V power supply

Cable included.



Ref: EBVV29

Notes:

- The references correspond to standard models: black ABS plastic casing, backlit LCD segment display, flat stainless steel plate and RS-232 and USB communications.
- Capacity / Accuracy: 6 kg / 2 g - 15 kg / 5 g.