


PS series



Dimensions



DATA IN mm

	PS-50	PS-70 I
A	235	230
B	240	300
C	130	130

Plate dimensions:
L230 x W190 mm.

Weight with packaging:
PS-50: 3.5 kg / PS-70 I: 4.2 kg.

CELY
PS SERIESLCD
SEGMENT
DISPLAYINTERNAL
RECHARGEABLE
BATTERYMETROLOGICAL
VERIFICATION
OPTIONAL (EU) IN
PS-50 FOR SOME
CAPACITIES

Characteristics and functionality

Main characteristics

- Weight only scale without printer.
- Internal rechargeable battery:
 - > Up to 70 hours' runtime for all the models, depending on conditions of use.
- IP65 protection equivalent (only in Cely PS-70 I).
- Valid for legal metrology (consult models).

Features

- Weighing.
- Units' change.
- Auto power off.
- Tare.

Capacity / Accuracy

- Cely PS-50: 3 kg / 0.5 g, 3 kg / 1 g, 6 kg / 1 g, 6 kg / 2 g, 15 kg / 2 g or 15 kg / 5 g.
- Cely PS-70 I: 6 kg / 2 g or 15 kg / 5 g.

Formats

- Flat.

Models

Cely PS-50

CAPACITY 3 kg / 0,5 g (mono-range)

Ref.: **71AOPS500001UE**

CAPACITY 6 kg / 1 g (mono-range)

Ref.: **71AOPS500002UE**

CAPACITY 15 kg / 2 g (mono-range)

Ref.: **71AOPS500003UE**

(M) not available

Cely PS-70 I

CAPACITY 6 kg / 2 g (mono-range)

Ref.: **71APS70I0005UE**

CAPACITY 15 kg / 5 g (mono-range)

Ref.: **71APS70I0006UE**

(M) not available

Options

Option	Characteristics	Ref.
Metrological verification (M)	Metrological verification (M), according to EU weighing directives. (See section on equipment metrological verification).	Consult

Note:

- The references correspond to standard models: White ABS plastic or stainless steel casing, backlit LCD segment display and flat stainless steel plate.

Capacity: Mono-range, from 3 up to 15 kg.

Construction

- Structure:
 - > PS-50: ABS plastic housing.
 - > PS-70 I: stainless steel housing.
- Console:
 - > PS-50: keypad with 3-keys and backlit LCD segment display of 5 digits (20 mm).
 - > PS-70 I: keypad with 3-keys and backlit LCD segment display of 4 digits (25 mm).
- Plate:
 - > Type: flat.
 - > Material: stainless steel.

Power supply

- Mains: 220 VAC with 12 V / 500 mA adapter.
- Internal rechargeable battery:
 - > 6 V / 4 Ah in PS-50.
 - > 6 V / 3.2 Ah in PS-70 I.

Energy consumption

- PS-50: 1.6 W (approx.) with backlight activated.
- PS-70 I: 1.8 W (approx.) with backlight activated.

CAPACITY 3 kg / 1 g (mono-range)

Ref.: **71AOPS51M004UE**

CAPACITY 6 kg / 2 g (mono-range)

Ref.: **71AOPS51M005UE**

CAPACITY 15 kg / 5 g (mono-range)

Ref.: **71AOPS51M006UE**

(M) optional